



SCAN CODE TO
WATCH VIDEO



Learn more about the
production of 182mm
Mono PV Solar Module

SKT385~410M10

385~410 Watt

182mm 108Cells All Black PV Module



MBB PERC
Half Cut Cell



Excellent Low-light
Performance



100% Inspection
Guarantee Reliability



Anti PID




Strengthened
Mechanical Load




High Density
Packaging





All Dimensions in mm
The above drawing is a graphical representation of the product.
For engineering quality drawings please contact SUNKET.



12 Years
Material & Craft
Quality assurance

12 Years
90% Output
Power guarantee

30 Years
80% Output
Power guarantee

Electrical Characteristics (STC/NOCT)

Module Type	SKT385M10		SKT390M10		SKT395M10		SKT400M10		SKT405M10		SKT410M10	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power- Pmax(W)	385	290	390	294	395	298	400	302	405	306	410	310
Open Circuit Voltage - Voc(V)	36.76	34.49	36.85	34.62	36.98	34.75	37.07	34.88	37.23	35.12	37.32	35.23
Short- Circuit Current - Isc(A)	13.53	10.82	13.61	10.89	13.70	10.96	13.79	11.03	13.87	11.10	13.95	11.16
Voltage at Pmax -Vmp(V)	30.44	28.66	30.64	28.87	30.84	29.08	31.01	29.26	31.21	29.47	31.45	29.72
Current at Pmax - Imp(A)	12.65	10.11	12.73	10.18	12.81	10.25	12.90	10.32	12.98	10.38	13.04	10.43
Module Efficiency -ηm(%)	19.8	/	20.0	/	20.2	/	20.5	/	20.8	/	21.0	/
Power Tolerance(W)	(0, +4.99W)											
Maximum System Voltage(V)	1500Vdc (IEC / UL)											
Maximum Series Fuse Rating (A)	25A											

STC : Irradiance 1000W/m², Cell Temperature 25 C, Air Mass 1.5

NOCT : Irradiance 800W/m², Ambient Temperature 20 C, Air Mass 1.5, Wind Speed 1m/s

Mechanical Specifications

External Dimensions	1722x1134x30mm
Weight	20.5g
Solar Cells	Mono crystalline 182mm (2x54pcs)
Front Glass	AR Coated 3.2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	1.2m
Connector	MC4 EVO2
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

Pmax Temperature Coefficient	-0.350%/ C
Voc Temperature Coefficient	-0.275%/ C
Isc Temperature Coefficient	+0.045%/ C
Operating Temperature	-40 ~ +85 C
Nominal Operating Cell Temperature(NOCT)	45±2 C

Packing Configuration

	1722x1134x30mm	
Container	20'GP	40'HQ
Pieces per Pallet	36	36
Pallets per Container	6	26
Pieces per Container	216	936

Current-Voltage & Power-Voltage Curves (SKT410M10)

